

UL Product iQ™



# OBJT2.E524975 - Single- and Multi-layer Insulated Winding Wire - Component

## Single- and Multi-layer Insulated Winding Wire - Component


SIHUI HENGHUI ELECTRICAL APPLIANCES CO LTD

E524975

Nanjiang Industrial Zone Dasha  
Sihui, Guangdong 526000 China

Cat. No.	Insulation Type	TIW Conductor Size Range	Temp Class °C	Rated Volts	Rated Volts	Rated Volts
				UL 60950-1 V peak	UL 60601-1 V peak	UL 61800-5-1 V rms
TIW-F*	Reinforced	0.1496-0.9930 mm	155(F)	1410	-	-

\* - \* - maybe leave blank or replaced by 2 letters (TC, MW or LZ) to indicate conductor type: Leave blank for bare copper conductor; replaced by  $\zeta$ TC $\zeta$  for tinned copper conductor; replaced by  $\zeta$ MW $\zeta$  for solid magnet wire as conductor, where solid magnet wire: UL recognized MW 79C, MW 80C, MW 82C, MW 83C; replaced by  $\zeta$ LZ $\zeta$  for stranded magnet wire as conductor.

Marking: Company name, material designation and the Recognized Component Mark,  On the smallest unit container in which the product is packaged, spool, or on a tag attached to the end of the wire.

Last Updated on 2022-01-18

并不是所有出现在本数据库中的公司名称和产品都满足了UL跟踪检验服务的要求。只有带有UL标志的产品，才应该被视为经过UL认证，并满足UL跟踪检验服务的要求。注意查看产品上的标志。

UL允许在线认证目录中所含材料的复制遵循以下条件：1.指南信息、装配、构造、设计、系统和/或认证（文件）必须在不得擅自任何数据（或图纸）的情况下完整且无误导性地呈现。2.经UL允许从在线认证目录转载声明必须出现在所摘录材料的邻近位置。此外，转载材料必须包含以下格式的版权声明：“© 2022 UL LLC”